



Brownwood Plywood

Our Brownwood Plywood is manufactured from South East Asia.

An economic product reflecting high recovery utilization of resource as peeling veneer yields high wood use to produce a high strength heavy weight stable flat panel.

Finishing can require high surface grain fill levels but resin absorption is low. Machines glues and works with tungsten tip cutters to minimize fibrous end grain.

Description

- This plywood is made from rotary peeled Keruing Hardwood
- The glue type Phenolic Formaldehyde WBP
- Pale brown colour
- Durable and hard wearing
- B/BB grade - B face veneer

Applications / Uses

- Heavy truck decks
- Furniture & cabinetry.
- Caravan and motor-home construction.
- Interior wall cladding.
- Letter boxes
- Window reveals
- Shop fitting & stage sets



Size and Thickness

Sheet size	2440 x 1220					
Thickness	3.6mm	6mm	9mm	12mm	18mm	28mm
# Layers	3	5	5	7	9	13
Weight per sheet (Kg)	8	12	19	25	35	57

Head Office -

27 Kioreroa Road, Whangarei (09 4389358)

email : office@bbstimbers.co.nz

Auckland Branch -

82 Henderson Valley Road, Henderson, Auckland (09 8360124)

email : phil@bbstimbers.co.nz

Christchurch Branch -

14 Halwyn Drive, Hei Hei , Christchurch (03 3445591)

email : andy@bbstimbers.co.nz

www.bbstimbers.co.nz